



7300 & 7305 MASTER VOLLEYBALL SYSTEM

E	MJP	9/16/22
D	MJP	03/15/22
C	RWP	06/04/08
B	ATS	04/22/05
A	MJB	12/17/03
REV	BY	DATE



Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

MASTER VOLLEYBALL SYSTEM

DRAWN	MJP	DATE	3/15/2022	DATE ISSUED	3/15/2022
APPROVED		DATE			
FILE LOC. Q:\Inventor Files\Specification Files\					
SIZE	SCALE	SHT. NO.	PART NO.		REV
A		1 OF 2	7300		E



MODEL 7300

MASTER VOLLEYBALL SYSTEM

RECOMMENDED APPLICATION

Top quality unit for use in high-level volleyball programs and showcase facilities. Meets all grade school, middle school, YMCA, club, USVBA, NFHS, and NCAA requirements for competitive play.

FLOOR SLEEVES AND COVER PLATES

Please refer to attached specification

UPRIGHTS

Upright post shall be 6063-T6 aluminum; 4" diameter post with weight of 34 lbs. Finish shall be gray anodize. Upright post shall be removable type with sleeves and covers a permanent fixture to the floor. Telescopic tube shall be 2-1/4" diameter aluminum tube. Net height shall be achieved by sliding the telescopic tube up or down and locking the telescopic tube in place with wedge type locking mechanism mounted on sliding rail. Telescopic tube to glide easily with spring assisted mechanism. Net heights range from 7'-0" to 7'-11 5/8". Post can collapse down to a total length of 8'-2 1/2". Upright post shall have high impact plastic caps on ends of the post for floor protection.

NET TENSIONER (WINCH)

The net tensioner shall incorporate a heavy duty, self-locking worm gear winch. A high tensile nylon strap will be used with the winch to achieve required net tension.

NET

Net features include 5/8" [16 mm] diameter fiberglass dowel and 4" [102 mm] square black nylon mesh (250 lbs [113 Kg] tensile strength) for excellent performance and durability. Free floating net along 5/32" [4.0 mm] diameter steel 7 x 19 cable (2,000 lbs [907 Kg] minimum breaking strength) allows for quick and easy centering of net about the court lines. Nylon straps with padded metallic clips are used to secure net in place. Net shall be 32' [9.75 m] length and 39" [99 m] width. Net perimeter shall have a 2" [51 mm] wide vinyl coated polyester hem that is double stitched. Net meets or exceeds all requirements for most levels of competition volleyball.

UPRIGHT PADS

Upright safety pads shall be one single piece 72" in height. Padding shall be constructed with 1 1/2" thick cross-linked polyethylene closed cell foam covered with 14-ounce nylon reinforced vinyl. Attachment to uprights shall be with Velcro® straps. Standard Colors are: white, yellow, orange, red, kelly green, forest green, royal blue, marine blue, navy blue, gray, black, maroon, beige, and purple.

NET ANTENNA AND TAPE

Net antenna shall be 3/8" diameter fiberglass rods 72" long with alternating red and white bands. Net tape shall be white nylon reinforced vinyl 2 1/2" wide with full-length pocket to accept the antenna. Attachment to net shall be full-length quick action Velcro® closures.

AVAILABLE OPTIONS

Center Post Uprights for multi-court applications
Referee Stand with optional padding
Storage Cart